



# ETN ISY-HOOK n° A.24.08620

## Modules validés – validated modules

Manufacturer	Module reference	Peak power		Length	Width	Thickness	Weight
		min	max				
<b>AIKO</b>	AIKO-Axxx-MAH54Db (2S+)	440 Wp	455 Wp	1722 mm	1134 mm	30 mm	24,0 kg
	AIKO-Axxx-MAH54Mb (2S)	445 Wp	460 Wp	1722 mm	1134 mm	30 mm	21,2 kg
<b>AKCOME</b>	SK8610HDGDC	380 Wp	400 Wp	1755 mm	1038 mm	30 mm	22,8 kg
<b>AMERISOLAR</b>	AS-7M108-HC-xxxW	400 Wp	415 Wp	1722 mm	1134 mm	30 mm	20,0 kg
<b>ASTRONERGY</b>	CHSM54N-HC	425 Wp	445 Wp	1722 mm	1134 mm	30 mm	21,3 kg
	CHSM54N(DG)/F-HC	425 Wp	440 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	CHSM54N(BL)/(BLH)-HC	420 Wp	440 Wp	1722 mm	1134 mm	30 mm	21,3 kg
	CHSM54N(DGT)/F-BH	415 Wp	430 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	CHSM54RNs(DG)/F-BH	435 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,5 kg
	<b>New</b> CHSM54RNs(DG)/F-BH (2mm+2mm)	445 Wp	465 Wp	1762 mm	1134 mm	30 mm	24,9 kg
	CHSM54RNs(DG)(BLH)/F-BH	430 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,5 kg
	CHSM54RNs(DG)(BLH)/F-BH (2mm+2mm)	440 Wp	460 Wp	1762 mm	1134 mm	30 mm	24,9 kg
	CHSM54RNs(DGT)(BLH)/F-BH	430 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,5 kg
	CHSM54RNs(DGT)(BLH)/F-BH (2mm+2mm)	440 Wp	460 Wp	1762 mm	1134 mm	30 mm	24,9 kg
	CHSM54RNs(DGT)/F-BH	430 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,5 kg
	CHSM60RNs(DGT)(BLH)/F-BH (2mm+2mm)	490 Wp	515 Wp	1961 mm	1134 mm	30 mm	27,4 kg
<b>Canadian Solar</b>	CS3L-XXXMS	360 Wp	385 Wp	1765 mm	1048 mm	35 mm	23,0 kg
	CS6R-xxxH-AG	405 Wp	430 Wp	1722 mm	1134 mm	30 mm	23,0 kg
	CS6R-xxxMS	395 Wp	420 Wp	1722 mm	1134 mm	30 mm	21,3 kg
<b>CellKraft</b>	CK500M-132	500 Wp	500 Wp	2094 mm	1134 mm	30 mm	29,0 kg
<b>DMEGC</b>	DMxxxM10-66HBB-V	485 Wp	500 Wp	2094 mm	1134 mm	35 mm	26,6 kg
	DMxxxM6-60HBW	375 Wp	385 Wp	1755 mm	1038 mm	35 mm	21,0 kg
	DMxxxM10RT-54HBW	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	20,6 kg
	DMxxxM10RT-54HBW-V	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	20,6 kg
	DMxxxM10RT-54HSW	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	20,6 kg
	DMxxxM10RT-54HSW-V	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	20,6 kg
	DMxxxM10RT-60HBB/HBB-V	480 Wp	500 Wp	1950 mm	1134 mm	30 mm	22,7 kg
	DMxxxM10RT-B54HBW	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	<b>New</b> DMxxxM10RT-B54HSW	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-B54HST	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-B54HBT	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-G54HBW	425 Wp	455 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-G54HSW	425 Wp	455 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-B60HBB	480 Wp	500 Wp	1950 mm	1134 mm	30 mm	27,1 kg
	DMxxxM10T-B54HSW	405 Wp	450 Wp	1722 mm	1134 mm	30 mm	23,6 kg
	DMxxxM10T-B54HBW	405 Wp	450 Wp	1722 mm	1134 mm	30 mm	23,6 kg
	DMxxxM10T-B54HST	405 Wp	450 Wp	1722 mm	1134 mm	30 mm	23,6 kg
	DMxxxM10T-B54HBT	405 Wp	450 Wp	1722 mm	1134 mm	30 mm	23,6 kg





# ETN ISY-HOOK n° A.24.08620

## Modules validés – validated modules

Manufacturer	Module reference	Peak power		Length	Width	Thickness	Weight
		min	max				
<b>DOMOS</b>	<b>DGE 500 BIV BF</b> <span style="border: 1px solid black; padding: 2px;">New</span>	480 Wp	515 Wp	1960 mm	1134 mm	30 mm	27,6 kg
<b>DualSun</b>	SPRING - DSTFxxx-108M10TB-03	420 Wp	430 Wp	1722 mm	1134 mm	30 mm	32,0 kg
	SPRING - DSTlxxx-108M10TB-03	420 Wp	430 Wp	1722 mm	1134 mm	30 mm	32,5 kg
	SPRING - DSTNxxx-108M10TB-03	420 Wp	430 Wp	1722 mm	1134 mm	30 mm	31,0 kg
	<b>FLASH - DSxxx-108M10RTB-03</b> <span style="border: 1px solid black; padding: 2px;">New</span>	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	FLASH - DSxxx-108M10TB-03	405 Wp	430 Wp	1722 mm	1134 mm	30 mm	25,1 kg
	FLASH - DSxxx-120M10TB-03	485 Wp	500 Wp	1950 mm	1134 mm	30 mm	27,1 kg
	FLASH - DSxxx-132M10-01	480 Wp	505 Wp	2094 mm	1134 mm	35 mm	26,0 kg
<b>DUONERGY</b>	ACN-120FB-HJT	375 Wp	375 Wp	1755 mm	1038 mm	40 mm	23,5 kg
	ACN-132FB-IBC	430 Wp	430 Wp	1895 mm	1039 mm	40 mm	28,0 kg
	DN-BB132-IBC	415 Wp	435 Wp	1895 mm	1039 mm	40 mm	28,0 kg
	DN-BT108N-2	395 Wp	435 Wp	1722 mm	1134 mm	30 mm	24,5 kg
	DN-BT120HJT-2	380 Wp	400 Wp	1755 mm	1038 mm	40 mm	23,5 kg
	DN-BT120HJT-A	375 Wp	395 Wp	1755 mm	1038 mm	30 mm	22,8 kg
	DN-BT108N-3	425 Wp	425 Wp	1722 mm	1134 mm	30 mm	23,6 kg
	DN-BT132N	500 Wp	500 Wp	2094 mm	1134 mm	30 mm	30,2 kg
	DN-BB132-IBC	430 Wp	430 Wp	1895 mm	1039 mm	30 mm	28,0 kg
<b>Eco Green Energy</b>	EGE-xxx-120M(M6)	350 Wp	375 Wp	1763 mm	1040 mm	35 mm	20,5 kg
	EGE-xxx-132M(M10)	500 Wp	500 Wp	2073 mm	1134 mm	35 mm	21,8 kg
	EGE-xxx-144M(M6)	445 Wp	455 Wp	2102 mm	1040 mm	35 mm	24,5 kg
<b>ECOYA</b>	JNMM120-xxx (L)	360 Wp	380 Wp	1755 mm	1038 mm	30 mm	19,3 kg
	JY3MxxxH60(H)	365 Wp	400 Wp	1755 mm	1038 mm	40 mm	20,0 kg
	TD-xxxMB-120HCxxx	360 Wp	375 Wp	1755 mm	1038 mm	30 mm	18,5 kg
<b>ET Solar</b>	ET-M660BHxxxBB	355 Wp	375 Wp	1755 mm	1138 mm	35 mm	20,0 kg
<b>FHE</b>	<b>FHE - 425W BV - MASTER</b>	425 Wp	425 Wp	1722 mm	1134 mm	30 mm	22,0 kg
	<b>FHE - 425W BVB - MASTER</b>	425 Wp	425 Wp	1722 mm	1134 mm	30 mm	22,0 kg
	<span style="border: 1px solid black; padding: 2px;">New</span> <b>FHE - 425W BVN - MASTER</b>	425 Wp	425 Wp	1722 mm	1134 mm	30 mm	22,0 kg
	<b>FHE - 500W SP - MASTER</b>	500 Wp	500 Wp	2094 mm	1134 mm	30 mm	26,0 kg
	<b>FHE - 500W - BVN - MASTER</b>	500 Wp	500 Wp	1961 mm	1134 mm	30 mm	27,6 kg
<b>French Solar Industry</b>	FSI120-xxx-M12	575 Wp	610 Wp	2172 mm	1303 mm	35 mm	30,9 kg
	FSI120-xxx-M6	375 Wp	375 Wp	1754 mm	1038 mm	30 mm	23,0 kg
	FSI-MC-108-BD	428 Wp	428 Wp	1721 mm	1133 mm	30 mm	22,0 kg
<b>Hyundai</b>	HiE-SxxxUF	375 Wp	375 Wp	1646 mm	1140 mm	35 mm	20,5 kg
	HiE-SxxxVG	390 Wp	410 Wp	1719 mm	1140 mm	35 mm	22,0 kg
<b>JNL SOLAR</b>	JLS108M	390 Wp	410 Wp	1724 mm	1134 mm	30 mm	21,5 kg
	JLS120M	360 Wp	380 Wp	1755 mm	1038 mm	30 mm	19,3 kg
	JLS120Mxxx - SUNMAX	360 Wp	380 Wp	1755 mm	1038 mm	30 mm	20,5 kg
	JLSDGxxxN-108M10 - Optimax	410 Wp	435 Wp	1722 mm	1134 mm	30 mm	23,3 kg





# ETN ISY-HOOK n° A.24.08620

## Modules validés – validated modules

Manufacturer	Module reference	Peak power		Length	Width	Thickness	Weight
		min	max				
<b>LONGi</b>	LR5-54HABB-xxxM	390 Wp	415 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	LR5-54HABD-xxxM	395 Wp	420 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	LR5-54HIBD-xxxM	390 Wp	425 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	LR5-54HIH-xxxM	400 Wp	415 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HPB-xxxM	400 Wp	420 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HPH-xxxM	405 Wp	425 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HTB-xxxM (Explorer)	410 Wp	430 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HTB-xxxM (Scientist)	435 Wp	445 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HTD-xxxM	415 Wp	440 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	<b>Exclusivity !</b> LR5-54HTDB-xxxM (Artist Ultra Black) <b>New</b>	415 Wp	430 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	LR5-54HTH-xxxM (Explorer)	415 Wp	435 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HTH-xxxM (Scientist)	440 Wp	450 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-66HPH-xxxM	495 Wp	515 Wp	2094 mm	1134 mm	35 mm	26,0 kg
	LR5-72HBD-xxxM (30mm)	540 Wp	560 Wp	2278 mm	1134 mm	30 mm	31,8 kg
	LR5-72HBD-xxxM (35mm) - 1133	530 Wp	550 Wp	2278 mm	1133 mm	35 mm	32,3 kg
	LR5-72HBD-xxxM (35mm) - 1134	540 Wp	560 Wp	2278 mm	1134 mm	35 mm	32,6 kg
	LR5-72HPH-xxxM	545 Wp	565 Wp	2278 mm	1134 mm	35 mm	27,5 kg
<b>RISEN</b>	Titan S G5.3 RSM40-8-xxxM	390 Wp	410 Wp	1754 mm	1096 mm	30 mm	21,5 kg
<b>SOLUXTEC</b>	DMMXSCNI-XXX	415 Wp	425 Wp	1722 mm	1133 mm	30 mm	21,5 kg
<b>TONGWEI</b>	THxxx-xxxPMB7-44SCF	400 Wp	425 Wp	1812 mm	1096 mm	30 mm	20,8 kg
	THxxx-xxxPMB7-44SCS	405 Wp	430 Wp	1812 mm	1096 mm	30 mm	20,8 kg
	THxxx-xxxPMB7-46SCF	420 Wp	445 Wp	1899 mm	1096 mm	30 mm	21,8 kg
	THxxx-xxxPMB7-46SCS	420 Wp	445 Wp	1899 mm	1096 mm	30 mm	21,8 kg
<b>Trina Solar</b>	TSM-xxxDE09.08	390 Wp	405 Wp	1754 mm	1096 mm	30 mm	21,0 kg
	TSM-xxxDE09R.05	405 Wp	425 Wp	1762 mm	1134 mm	30 mm	21,8 kg
	TSM-xxxDE09R.08	415 Wp	435 Wp	1762 mm	1134 mm	30 mm	21,8 kg
	TSM-xxxDE18M(II)	485 Wp	510 Wp	2187 mm	1102 mm	35 mm	26,5 kg
	TSM-xxxNEG9R.28	415 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,8 kg

### Service client – Customer service

+33.4.12.32.77.80 | [contact@isy-pv.com](mailto:contact@isy-pv.com)

### Support Technique – Technical support

+33.6.65.65.88.86 | [technique@isy-pv.com](mailto:technique@isy-pv.com)



SAS ISY-PV - 20 AVENUE DU PIC DE BERTAGNE - 13420 - GEMENOS (04.42.32.77.80)  
Capital 100 000 € - RCS Marseille B - SIRET 928 271 220 00016 - FR 29 928 271 220

