

Certificate of Conformity

Certificate Number: CN-PV-210064

On the basis of the tests undertaken, the samples of the below product have been found to comply with the requirements of the referenced specifications /standards at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture. The manufacturer shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant:	Shenzhen SOFARSOLAR Co., Ltd. 401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen, China.
Product:	Solar Grid-tied Inverter
Ratings & Principle Characteristics:	See Appendix to Certificate of Conformity
Models:	SOFAR 3.3KTLX-G3, SOFAR 4.4KTLX-G3, SOFAR 5KTLX-G3-A SOFAR 5.5KTLX-G3, SOFAR 6.6KTLX-G3, SOFAR 8.8KTLX-G3, SOFAR 8.8KTLX-G3-A, SOFAR 11KTLX-G3, SOFAR 10KTLX-G3-A SOFAR 11KTLX-G3-A, SOFAR 12KTLX-G3
Brand Name:	SSEAR
Tested according to:	C10/11: ed.2.1, 01 Sep 2019 SPECIFIC TECHNICAL PRESCRIPTIONS REGARDING POWER-GENERATING PLANTS OPERATING IN PARALLEL TO THE DISTRIBUTION NETWORK Type approved for type A
Certificate Issuing Office Name & Address:	Intertek Testing Services Ltd. Shanghai West Area, 2 nd Floor, No. 707, Zhangyang Road China (Shanghai) Pilot Free Trade Zone, Shanghai, P. R. China
Test Reports No: Additional information in A	210416108GZU-005 Appendix.

(mustu

Signature

Certification Manager: Grady Ye Date: 20 April 2021

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210064

MODEL	SOFAR 3.3KTLX- G3	SOFAR 4.4KTLX- G3	SOFAR 5KTLX- G3-A	SOFAR 5.5KTLX- G3
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15/15A			
PV lsc	22.5/22.5A			
Rated power(W)	3000	4000	5000	5000
Max.apparent power (VA)	3300	4400	5000	5500
Max output current	3×5.0 A	3×6.7 A	3×7.6 A	3×8.3 A
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency	50 Hz			
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	-30℃ - +60℃			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210064

MODEL	SOFAR 6.6KTLX- G3	SOFAR 8.8KTLX- G3	SOFAR 8.8KTLX- G3-A	SOFAR 10KTLX- G3-A	
Max PV voltage	1100Vdc				
MPPT Voltage range	140-1000Vdc				
Max. input current	15/15A		15/30A		
PV lsc	22.5/22.5A		22.5A/45A		
Rated power(W)	6000	8000	8000	10000	
Max.apparent power (VA)	6600	8800	8800	10000	
Max output current	3×10.0 A	3×13.3 A	3×13.3 A	3×15.2 A	
Output voltage	3W/N/PE 230Vac/400Vac				
Nominal Frequency	50 Hz				
Power Factor	1 default (adjustable+/-0.8)				
Ambient Temperature	-30℃ - +60℃				
Protection Degree	IP65				
Protection Class	Class I				
Software Version	V000001				

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210064

MODEL	SOFAR 11KTLX-G3	SOFAR 11KTLX-G3-A	SOFAR 12KTLX-G3	
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15A/15A 15A/30A			
PV lsc	22.5/22.5A 22.5A/45A			
Rated power(W)	10000	10000	12000	
Max.apparent power (VA)	11000	11000	13200	
Max output current	3×16.7 A	3×16.7 A	3×20.0 A	
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency		50 Hz		
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	-30℃ - +60℃			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.