



# ETN ISY-RAIL n° A.24.09151

## Modules validés – validated modules

**New**

Manufacturer	Module reference	Peak power		Length	Width	Thickness	Weight
		min	max				
<b>Canadian Solar</b>	CS6R-xxxMS	395 Wp	420 Wp	1722 mm	1134 mm	30 mm	21.3 kg
<b>DMEGC</b>	DMxxxM10-66HBB-V	485 Wp	500 Wp	2094 mm	1134 mm	35 mm	26.6 kg
	DMxxxM10RT-60HBB/HBB-V	480 Wp	500 Wp	1950 mm	1134 mm	30 mm	22.7 kg
	DMxxxM10RT-B54HBT	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24.5 kg
	DMxxxM10RT-G54HBW	425 Wp	455 Wp	1762 mm	1134 mm	30 mm	24.5 kg
	DMxxxM10RT-G54HSW	425 Wp	455 Wp	1762 mm	1134 mm	30 mm	24.5 kg
	DMxxxM10RT-B60HBT	490 Wp	510 Wp	1950 mm	1134 mm	30 mm	26.8 kg
<b>DOMOS</b>	DM 375 HC FullBlack	375 Wp	375 Wp	1763 mm	1040 mm	35 mm	20.5 kg
	DGE 500 BIV BF	480 Wp	515 Wp	1960 mm	1134 mm	30 mm	27.6 kg
<b>DualSun</b>	FLASH - DSxxx-108M10RTB-03	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24.5 kg
	FLASH - DSxxx-108M10TB-03	405 Wp	430 Wp	1722 mm	1134 mm	30 mm	25.1 kg
	FLASH - DSxxx-120M10TB-03	485 Wp	500 Wp	1950 mm	1134 mm	30 mm	27.1 kg
<b>DUONERGY</b>	ACN-120FB-HJT	375 Wp	375 Wp	1755 mm	1038 mm	40 mm	23.5 kg
	DN-BT108N-2	395 Wp	435 Wp	1722 mm	1134 mm	30 mm	24.5 kg
	DN-BT108N-3	425 Wp	425 Wp	1722 mm	1134 mm	30 mm	23.6 kg
	DN-BT108N-4	450 Wp	450 Wp	1762 mm	1134 mm	30 mm	24.5 kg
	DN-BT120N-1	500 Wp	500 Wp	1950 mm	1134 mm	30 mm	26.8 kg
<b>Eco Green Energy</b>	EGE-xxx-120M(M6)	350 Wp	375 Wp	1763 mm	1040 mm	35 mm	20.5 kg
	EGE-xxx-132M(M10)	500 Wp	500 Wp	2073 mm	1134 mm	35 mm	21.8 kg
<b>JNL SOLAR</b>	JLS108M	390 Wp	410 Wp	1724 mm	1134 mm	30 mm	21.5 kg
	JLS120Mxxx - SUNMAX	360 Wp	380 Wp	1755 mm	1038 mm	30 mm	20.5 kg
	JLSDGxxxN-108M10 - Optimax - transparent	415 Wp	440 Wp	1722 mm	1134 mm	30 mm	23.3 kg
	JLSDGxxxN-108M10 - Optimax - FB	410 Wp	440 Wp	1722 mm	1134 mm	30 mm	23.3 kg
<b>LONGi</b>	LR5-54HTB-xxxM (Explorer)	410 Wp	430 Wp	1722 mm	1134 mm	30 mm	20.8 kg
	LR5-54HTB-xxxM (Scientist)	435 Wp	445 Wp	1722 mm	1134 mm	30 mm	20.8 kg
	LR5-54HTDB-xxxM (Artist Ultra Black)	415 Wp	430 Wp	1722 mm	1134 mm	30 mm	22.5 kg
	LR5-54HTH-xxxM (Explorer)	415 Wp	435 Wp	1722 mm	1134 mm	30 mm	20.8 kg
	LR5-54HTH-xxxM (Scientist)	440 Wp	450 Wp	1722 mm	1134 mm	30 mm	20.8 kg
<b>Trina Solar</b>	TSM-xxxNEG9R.28	415 Wp	450 Wp	1762 mm	1134 mm	30 mm	21.8 kg
	TSM-xxxNEG18R.28	500 Wp	500 Wp	1961 mm	1134 mm	30 mm	23.5 kg

**Service client – Customer service**

+33.4.42.32.77.80 | [contact@isy-pv.com](mailto:contact@isy-pv.com)

**Support Technique – Technical support**

+33.6.65.65.88.86 | [technique@isy-pv.com](mailto:technique@isy-pv.com)



SAS ISY-PV - 20 AVENUE DU PIC DE BERTAGNE - 13420 - GEMENOS (04.42.32.77.80)  
Capital 100 000 € - RCS Marseille B - SIRET 928 271 220 00016 - FR 29 928 271 220

