



## SUN2000 12-25KTL-MB0 Harmonics Testing Data

400V/50Hz/100%Pn

| Order | Harmonic current | Order | Harmonics current |
|-------|------------------|-------|-------------------|
|       | % of In          |       | % of In           |
| 2     | 0.123            | 3     | 0.177             |
| 4     | 0.077            | 5     | 0.544             |
| 6     | 0.05             | 7     | 0.171             |
| 8     | 0.047            | 9     | 0.088             |
| 10    | 0.044            | 11    | 0.221             |
| 12    | 0.036            | 13    | 0.323             |
| 14    | 0.047            | 15    | 0.064             |
| 16    | 0.039            | 17    | 0.326             |
| 18    | 0.041            | 19    | 0.638             |
| 20    | 0.039            | 21    | 0.055             |
| 22    | 0.033            | 23    | 0.434             |
| 24    | 0.036            | 25    | 0.39              |
| 26    | 0.033            | 27    | 0.05              |
| 28    | 0.028            | 29    | 0.365             |
| 30    | 0.036            | 31    | 0.309             |
| 32    | 0.03             | 33    | 0.055             |
| 34    | -                | 35    | -                 |
| 36    | -                | 37    | -                 |
| 38    | -                | 39    | -                 |
| 40    | -                | 41    | -                 |
| 42    | -                | 43    | -                 |
| 44    | -                | 45    | -                 |
| 46    | -                | 47    | -                 |
| 48    | -                | 49    | -                 |
| 50    | -                |       |                   |

Boulogne-Billancourt, 13/03/2024



HUAWEI TECHNOLOGIES FRANCE SASU  
Arcs de Seine – 18 quai du point du jour  
92100 Boulogne-Billancourt